



**Presión Nominal 16**

Paso Nominal	Brida			d <sub>s</sub> máx.	Tomillos			Pesos	
	D	b	k		número	rosca	d <sub>2</sub>	forma B	forma T
10	90	14	60		4	M 12	14	0.63	
15	95	14	65					0.72	
20	105	16	75					1.01	
25	115	16	85					1.23	
32	140	16	100					1.80	
40	150	16	110					2.09	
50	165	18	125					2.88	
65	185	18	145	55	8	M 16	18	3.66	3.70
80	200	20	160	70				4.77	4.83
100	220	20	180	90				5.65	5.75
125	250	22	210	115				8.42	8.59
150	285	22	240	140				10.4	10.6
175	315	24	270	165				14.0	14.3
200	340	24	295	190				16.1	16.5
250	405	26	355	235	12	M 24	26	24.9	25.6
300	460	28	410	285				35.1	36.1
350	520	30	470	330				47.8	49.1
400	580	32	525	380	16	M 27	30	63.5	65.3
500	715	36	650	475				20	M 30

**Presión Nominal 25**

Paso Nominal	Brida			d <sub>s</sub> máx.	Tomillos			Pesos	
	D	b	k		número	rosca	d <sub>2</sub>	forma B	forma T
10 hasta 150	Para pasos nominales de 10 hasta 150 se emplarán bridas ciegas de la presión nominal 40								
175	330	28	280	165	12	M 24	26	17.8	17.6
200	360	30	310	190				22.3	22.7
250	425	32	370	237				33.5	34.2
300	485	34	430	285	16	M 27	30	46.3	47.3
350	555	38	490	332				68.0	69.3
400	620	40	550	380				89.7	91.5
500	730	45	660	475	20	M 33	36	138	141