



Presión Nominal 40

Paso Nominal	Brida			d ₃ máx.	Tomillos			Pesos	
	D	b	k		número	rosca	d ₂	forma B	forma T
10	90	16	60		4	M 12	14	0.72	
15	95	16	65					0.81	
20	105	18	75					1.24	
25	115	18	85					1.38	
32	140	18	100			2.03			
40	150	18	110			2.35			
50	165	20	125			3.20			
65	185	22	145	55	8	M 16	18	4.29	4.33
80	200	24	160	70				5.88	5.94
100	235	24	190	90				M 20	22
125	270	26	220	115	8	M 24	26	10.8	11.0
150	300	28	250	140				14.5	14.7
175	350	32	295	165	12	M 27	30	22.1	22.4
200	375	34	320	190				27.2	27.6
250	450	38	385	235				M 30	33
300	515	42	450	285	16	M 33	36	63.3	64.3
350	580	46	510	330				89.5	90.8
400	660	50	585	380				127	129
500	755	56	670	475				M 36	39
					20	M 39	42	172	175

Presión Nominal 64

Paso Nominal	Brida			d ₂	d ₁	d ₃ máx.	f	Tomillos			Pesos Kg
	D	b	k					número	rosca	d ₂	
10 hasta 40	Para pasos nominales de 10 hasta 40 se emplearán bridas ciegas de la presión nominal 100										
50	180	26	135	82	102	-	3	4	M 20	22	4.51
65	205	26	160	98	122	45					5.71
80	215	28	170	112	138	60					6.92
100	250	30	200	138	162	80					10.1
125	295	34	240	168	188	105		16.0			
150	345	36	280	202	218	130		23.5			
175	375	40	310	228	260	155		30.8			
200	415	42	345	256	285	180		39.7			
250	470	46	400	316	345	220		57.4			
300	530	52	460	372	410	270		81.0			
350	600	56	525	420	465	310	4	16	M 36	39	114
400	670	60	585	475	535	360					M 39